

10092704.030700

SPECIFICATION

TO ALL WHOM IT MAY CONCERN:

BE IT KNOWN THAT WE, TSUNEO MAKI, a citizen of Japan residing at Kanagawa, Japan and KAZUNORI BANNAI, a citizen of Japan residing at Tokyo, Japan have invented certain new and useful improvements in

RECORDING-MEDIUM CONVEYING DEVICE CONVEYING  
A RECORDING MEDIUM ON A CONVEYING BELT CHARGED WITH  
A POSITIVE CHARGE AND A NEGATIVE CHARGE ALTERNATELY

of which the following is a specification:-

BACKGROUND OF THE INVENTION

1. Field of the Invention

The present invention generally relates to a conveying device conveying a recording medium, such as a recording sheet, on which an image is printed by jetting a liquid such as an ink thereto, a conveyance control device, and an inkjet recording device printing such an image on the recording medium, and more particularly, to a conveying device which can convey the recording medium with high precision so as to increase a positional precision of applying the liquid onto the recording medium to stably form a high-quality image on the recording medium.

2. Description of the Related Art

A full-colored image can be formed by an electrophotographic method including steps of forming an electrostatic latent image on a photosensitive member, developing each color, and then overlapping the developed colors. However, in performing this method, the step of overlapping the colors is difficult. Further, the method involves complicated component devices including developing devices around the photosensitive member, which enlarges an image-forming device as a whole, and increases costs thereof. By contrast, with an inkjet recording device printing on a

recording sheet by jetting ink drops thereon, it is easy to overlap the colors. Additionally, the inkjet recording device has a small recording head jetting the ink drops, which reduces the size of the image-forming device as a whole. Also, the inkjet recording device is excellent in terms of a photographic quality. Further, an image formed on an OHP by the inkjet recording device has an excellent optical transmittance.

In pursuit of a higher-quality image in this inkjet recording device, the ink drops need to be jetted to landing spots on the recording sheet with higher precision. Therefor, not only the recording head jetting the ink drops needs to be further sophisticated in structure, but also the recording sheet needs to be conveyed with higher precision. In a serial printer of an inkjet type, the recording sheet is stopped while the recording head performs a scanning. Accordingly, the recording sheet is repeatedly conveyed and stopped. At this point, a precision of conveying the recording sheet means conveying the recording sheet a predetermined distance, and thereafter stopping the recording sheet at a predetermined position.

For the purpose of enhancing the precision of conveying the recording sheet, in inkjet recording devices disclosed in Japanese Laid-Open Patent

Application No. 4-201469, Japanese Laid-Open Patent  
Application No. 9-254460, and Japanese Laid-Open Patent  
Application No. 2000-25249, for example, a conveying  
belt conveying the recording sheet is uniformly charged  
5 positively so that the recording sheet is stick fast to  
the conveying belt by an electrostatic force so as to  
prevent the recording sheet from being displaced.  
However, in this state, the ink drops jetted from the  
recording head are influenced by an electric field such  
10 that landing spots of the ink drops are displaced on the  
recording sheet. For the purpose of preventing this  
displacement of the landing spots of the ink drops, a  
negative charge is applied to the conveying belt  
uniformly charged positively on the surface, in the  
15 vicinity of the recording head so as to lessen the  
electrostatic force so that the ink drops jetted from  
the recording head are not influenced by the electric  
field, as described in Japanese Laid-Open Patent  
Application No. 2000-25249, for example. Additionally,  
20 as described in Japanese Laid-Open Patent Application No.  
4-201469, for example, a circumferential groove is  
formed at a predetermined position in an axial direction  
of a conveying roller, and a projection is formed at a  
position in a widthwise direction of the conveying belt  
25 wound around the conveying roller, the position

corresponding to the circumferential groove of the conveying roller, wherein the projection of the conveying belt is engaged in the circumferential groove of the conveying roller so as to regulate the widthwise position of the conveying belt.

However, applying the negative charge, as mentioned above, to the conveying belt in the vicinity of the recording head so as to lessen the electrostatic force necessitates a means therefor, which disadvantageously complicates an entire structure of a conveying device conveying the recording sheet. Additionally, after an image is recorded on the recording sheet by jetting the ink drops thereon, separating the recording sheet from the conveying belt necessitates a separating force that exceeds the electrostatic force applied throughout the surface of the recording sheet, which makes it difficult to provide a separating unit capable of separating the recording sheet. Further, when the conveying belt slips on the conveying roller, the recording sheet is displaced in a direction in which the recording sheet is conveyed by the conveying belt, reducing the precision of conveying the recording sheet.

Additionally, when an image is recorded on the recording sheet by jetting the ink drops thereon, the

recording sheet is elongated due to water contained in the ink drops. This phenomenon is referred to as a cockling. Due to this cockling, the recording sheet becomes wavery such that the distance between nozzles of the recording head and the surface of the recording sheet varies depending on the position. When this cockling becomes aggravated, the recording sheet contacts the nozzles of the recording head, at worst, such that the nozzles of the recording head become dirty, and that the recording sheet is smeared. Further, this cockling may displace the landing spots of the ink drops on the recording sheet. In order to prevent these influences of the cockling, an image is formed on a recessed platen by jetting the ink drops from the recording head thereon, while the recording sheet is pressed by a spur having projections on its periphery. However, pressing the recording sheet by the spur may leave a scar on the image formed on the recording sheet, resulting in a deterioration of the image. Also, in order to prevent the above-mentioned influences of the cockling, there is another measure as described in Japanese Laid-Open Patent Application No. 2000-191175. According to this measure, protruding parts and recessing parts are formed on the surface of the conveying belt. The recessing parts are provided with

air inflow ports. Vacuum suction is performed via these  
air inflow ports so as to vacuum-suck the recording  
sheet to the conveying belt. Thereby, the waves  
occurring in the recording sheet undergoing the above-  
5 mentioned cockling are made lower such that the  
recording sheet does not contact the recording head.

However, when the recording sheet is vacuum-  
sucked by the recessing parts of the conveying belt so  
as to prevent the above-mentioned influences of the  
10 cockling of the recording sheet, the recording sheet in  
the vicinity of the recording head also becomes uneven  
according to the protruding parts and recessing parts  
formed on the surface of the conveying belt. This  
unevenness on the recording sheet displaces the landing  
15 spots of the ink drops on the recording sheet, which  
results in a deteriorated image.

Further, there is also an inkjet recording  
device comprising a pair of conveying rollers, one of  
the pair being a combination of the above-mentioned spur  
20 and a roller, in which the pair of the conveying rollers  
convey the recording sheet. In this device, the  
precision of conveying the recording sheet can be  
guaranteed only when the recording sheet engages the  
pair of the conveying rollers. In recent years, there  
25 has been a need for an expansion of an image printing

20090704.030700

area. For the purpose of securing this printing area,  
there is also an inkjet recording device forming an  
image in a state that cannot essentially guarantee the  
precision of conveying the recording sheet, i.e., in a  
5 state where the recording sheet engages only either of  
the pair of the conveying rollers. When an elevation of  
the recording sheet occurs in this state, the inkjet  
recording device is unable to deal with this elevation,  
and cannot secure a force for conveying the recording  
10 sheet; thereby, the precision of conveying the recording  
sheet cannot be guaranteed, and a quality of an image is  
reduced.

#### SUMMARY OF THE INVENTION

15 It is a general object of the present  
invention to provide an improved and useful recording-  
medium conveying device, a conveyance control device,  
and an inkjet recording device, in which the above-  
mentioned problems are eliminated.

20 A more specific object of the present  
invention is to provide a recording-medium conveying  
device, a conveyance control device, and an inkjet  
recording device, which can enhance a precision of  
conveying a recording sheet with a simple configuration,  
25 and can expand an printing area of the recording sheet



while stably forming a high-quality image.

In order to achieve the above-mentioned objects, there is provided according to one aspect of the present invention a recording-medium conveying device conveying a recording medium to an image recording part, the recording medium being separated and fed from a recording-medium feeding device, the recording-medium conveying device comprising:

a conveying belt wound around a driving roller and a driven roller so as to convey the recording medium to the image recording part, the conveying belt having an insulating layer formed at at least a side contacting the recording medium; and

a belt charging unit provided in contact with the conveying belt so as to charge the conveying belt with a positive charge and a negative charge alternately in a moving direction of the conveying belt by applying an AC bias to the conveying belt.

According to the present invention, a micro electric field is induced from the positive charge to the negative charge charged in the conveying belt. This micro electric field causes the recording medium to stick fast electrostatically to the conveying belt. Accordingly, the recording medium can be stably conveyed to the image recording part. Additionally, the

10092701-030702

recording medium can be conveyed while the evenness of a  
print surface thereof is maintained without being  
pressed by a spur, etc. Therefore, not only a high-  
quality image can be stably formed on the recording  
5 medium, but also the print surface of the recording  
medium can be prevented from being smeared or damaged.

Additionally, in the recording-medium  
conveying device according to the present invention, the  
belt charging unit may preferably apply the AC bias to  
10 the conveying belt while the conveying belt conveys the  
recording medium, and the belt charging unit may  
preferably stop applying the AC bias to the conveying  
belt while the conveying belt stops conveying the  
recording medium.

15 According to the present invention, this  
function of stopping the application of the AC bias  
prevents the AC bias from removing the charges charged  
in the conveying belt, and also prevents charges from  
being charged in unintended directions.

20 Additionally, in the recording-medium  
conveying device according to the present invention, the  
belt charging unit may apply the AC bias to the  
conveying belt while the conveying belt is continuously  
revolved, before the conveying belt conveys the  
25 recording medium.

According to the present invention, the positive charge and the negative charge can be stably charged in the conveying belt.

Additionally, in the recording-medium  
5 conveying device according to the present invention, the conveying belt may be formed of one layer of the insulating layer, or may be formed of two layers composed of the insulating layer formed at one side contacting the recording medium and a conductive layer  
10 formed at the other side not contacting the recording medium.

According to the present invention, the positive charge and the negative charge charged by applying the AC bias can be stably retained in the  
15 insulating layer of the conveying belt.

Additionally, in the recording-medium conveying device according to the present invention, the insulating layer may have a volume resistivity equal to or more than  $10^{12} \Omega\text{cm}$ , preferably  $10^{15} \Omega\text{cm}$ .

20 According to the present invention, the positive charge and the negative charge alternately charged in the insulating layer are prevented from moving across boundaries therebetween so that the insulating layer can be charged stably with the positive  
25 charge and the negative charge alternately.

Additionally, the recording-medium conveying device according to the present invention may further comprise conveyance guides provided at both sides of the conveying belt in a widthwise direction thereof so as to  
5 guide the recording medium, the conveying belt being formed narrower than the recording medium.

According to the present invention, the conveyance guides prevent an elevation of the recording medium soaking the ink drops, and thereby prevents a  
10 displacement of landing spots of the ink drops on the recording medium.

Additionally, in the recording-medium conveying device according to the present invention, the conveyance guides may comprise a plurality of ribs and  
15 recession grooves alternately, each of the ribs and the recession grooves being aligned along a conveying direction of the recording medium.

According to the present invention, parts of the elongated recording medium soaking the ink drops sag  
20 into the recession grooves where the ribs do not exist. This prevents an elevation of the recording medium soaking the ink drops.

Additionally, the recording-medium conveying device according to the present invention may further  
25 comprise a pressing roller pressing the conveying belt

10092701-00000

against the driving roller by exerting an elastic force so as to prevent the conveying belt from slipping on the driving roller.

According to the present invention, not only  
5 the conveying belt is prevented from slipping on the driving roller, the recording medium stuck electrostatically to the conveying belt can be pressed closely against the conveying belt 214 so that the recording medium adheres further firmly to the conveying  
10 belt electrostatically.

Additionally, in the recording-medium conveying device according to the present invention, the pressing roller may be provided at a position downstream in a revolving direction of the driving roller.

15 According to the present invention, the recording medium can be surely stuck fast to the conveying belt at the image recording part including a recording head so as to be conveyed with higher precision.

20 Additionally, in the recording-medium conveying device according to the present invention, at least the driving roller among the driving roller and the driven roller may have a plurality of projections on a surface thereof. Preferably, the conveying belt may  
25 be formed of a timing belt.

10092701-0000

According to the present invention, the conveying belt can be more surely prevented from slipping on the driving roller or the driven roller.

In order to achieve the above-mentioned objects, there is also provided according to another aspect of the present invention a recording-medium conveying device conveying a recording medium to an image recording part, the recording medium being separated and fed from a recording-medium feeding device by a separating unit thereof, the recording-medium conveying device comprising:

a conveying belt wound around a driving roller and a driven roller so as to convey the recording medium to the image recording part, the conveying belt having a two-layer structure composed of an insulating layer formed at one side contacting the recording medium and a conductive layer formed at the other side not contacting the recording medium;

a belt charging unit provided in contact with the insulating layer in a vicinity of the separating unit so as to charge the insulating layer with a positive charge and a negative charge alternately in a moving direction of the conveying belt by applying an AC bias to the conveying belt; and

a pressing roller pressing the conveying belt

against the driving roller by exerting an elastic force so as to prevent the conveying belt from slipping on the driving roller.

In order to achieve the above-mentioned  
5 objects, there is also provided according to another aspect of the present invention a recording-medium conveying device conveying a recording medium to an image recording part, the recording medium being separated and fed from a recording-medium feeding device  
10 by a separating unit thereof, the recording-medium conveying device comprising:

a conveying belt wound around a central part of a driving roller and a central part of a driven roller so as to convey the recording medium to the image  
15 recording part, the conveying belt being narrower than the recording medium, and having a two-layer structure composed of an insulating layer formed at one side contacting the recording medium and a conductive layer formed at the other side not contacting the recording  
20 medium;

conveyance guides provided at both sides of the conveying belt in a widthwise direction thereof in the image recording part, the conveyance guides having a plurality of ribs and recession grooves alternately,  
25 each of the ribs and the recession grooves being aligned

10092701-0300E

along a conveying direction of the recording medium;

a belt charging unit provided in contact with the insulating layer in a vicinity of the separating unit so as to charge the insulating layer with a  
5 positive charge and a negative charge alternately in a moving direction of the conveying belt by applying an AC bias to the conveying belt; and

a pressing roller pressing the conveying belt against the driving roller by exerting an elastic force  
10 so as to prevent the conveying belt from slipping on the driving roller.

Additionally, in the recording-medium conveying device according to the present invention, a surface of the driving roller may be cured, for example,  
15 by being coated with urethane.

In order to achieve the above-mentioned objects, there is also provided according to another aspect of the present invention a recording-medium conveying device conveying a recording medium to an  
20 image recording part, the recording medium being separated and fed from a recording-medium feeding device by a separating unit thereof, the recording-medium conveying device comprising:

a conveying belt wound around a driving roller  
25 and a driven roller so as to convey the recording medium

10092701.030702



to the image recording part, the conveying belt having a two-layer structure composed of an insulating layer formed at one side contacting the recording medium and a conductive layer formed at the other side not contacting the recording medium; and

5 a belt charging unit provided in contact with the insulating layer in a vicinity of the separating unit so as to charge the insulating layer with a positive charge and a negative charge alternately in a moving direction of the conveying belt by applying an AC bias to the conveying belt,

wherein at least one of the driving roller and the driven roller is a grip roller having a plurality of projections.

15 In order to achieve the above-mentioned objects, there is also provided according to another aspect of the present invention a recording-medium conveying device conveying a recording medium to an image recording part, the recording medium being separated and fed from a recording-medium feeding device by a separating unit thereof, the recording-medium conveying device comprising:

20 a conveying belt wound around a central part of a driving roller and a central part of a driven roller so as to convey the recording medium to the image

10092701-030702

recording part, the conveying belt being narrower than the recording medium, and having a two-layer structure composed of an insulating layer formed at one side contacting the recording medium and a conductive layer  
5 formed at the other side not contacting the recording medium;

conveyance guides provided at both sides of the conveying belt in a widthwise direction thereof in the image recording part, the conveyance guides having a  
10 plurality of ribs and recession grooves alternately, each of the ribs and the recession grooves being aligned along a conveying direction of the recording medium; and

a belt charging unit provided in contact with the insulating layer in a vicinity of the separating  
15 unit so as to charge the insulating layer with a positive charge and a negative charge alternately in a moving direction of the conveying belt by applying an AC bias to the conveying belt,

wherein at least one of the driving roller and  
20 the driven roller is a grip roller having a plurality of projections.

In order to achieve the above-mentioned objects, there is also provided according to another aspect of the present invention a recording-medium  
25 conveying device conveying a recording medium to an

10092701.030702

image recording part, the recording medium being separated and fed from a recording-medium feeding device by a separating unit thereof, the recording-medium conveying device comprising:

5           a conveying belt wound around a driving roller and a driven roller so as to convey the recording medium to the image recording part, the conveying belt having a two-layer structure composed of an insulating layer formed at one side contacting the recording medium and a  
10 timing belt formed by a conductive layer at the other side not contacting the recording medium; and

          a belt charging unit provided in contact with the insulating layer in a vicinity of the separating unit so as to charge the insulating layer with a  
15 positive charge and a negative charge alternately in a moving direction of the conveying belt by applying an AC bias to the conveying belt.

          In order to achieve the above-mentioned objects, there is also provided according to another  
20 aspect of the present invention a recording medium to an image recording part, the recording medium being separated and fed from a recording-medium feeding device by a separating unit thereof, the recording-medium conveying device comprising:

25           a conveying belt wound around a central part

10092701-030200

of a driving roller and a central part of a driven roller so as to convey the recording medium to the image recording part, the conveying belt being narrower than the recording medium, and having a two-layer structure  
5 composed of an insulating layer formed at one side contacting the recording medium and a timing belt formed by a conductive layer at the other side not contacting the recording medium; and

conveyance guides provided at both sides of  
10 the conveying belt in a widthwise direction thereof in the image recording part, the conveyance guides having a plurality of ribs and recession grooves alternately, each of the ribs and the recession grooves being aligned along a conveying direction of the recording medium; and  
15 a belt charging unit provided in contact with the insulating layer in a vicinity of the separating unit so as to charge the insulating layer with a positive charge and a negative charge alternately in a moving direction of the conveying belt by applying an AC  
20 bias to the conveying belt.

Additionally, in the recording-medium conveying device according to the present invention, the timing belt may be formed at at least a part of the other side of the conveying belt.

25 Additionally, in the recording-medium

conveying device according to the present invention, one of the driving roller and the driven roller positioned upstream in the conveying direction of the recording medium may have a large diameter, and the other of the driving roller and the driven roller positioned downstream in the conveying direction of the recording medium may have a small diameter.

In order to achieve the above-mentioned objects, there is also provided according to another aspect of the present invention a recording-medium conveying device conveying a recording medium to an image recording part, the recording medium being separated and fed from a recording-medium feeding device, the recording-medium conveying device comprising:

a conveying belt wound around a driving roller and a driven roller, the driving roller being connected to a ground, so as to convey the recording medium to the image recording part, the conveying belt having an insulating layer formed at a side contacting the recording medium;

a belt charging unit provided opposite the driving roller at a position upstream in a revolving direction of the driving roller from a position at which the recording medium fed from the recording-medium feeding device contacts the conveying belt wound around

the driving roller so as to charge the conveying belt with a positive charge and a negative charge alternately in a moving direction of the conveying belt by applying an AC bias to the conveying belt; and

5 a pressing roller provided opposite the driving roller at a position downstream in the revolving direction of the driving roller from the belt charging unit so as to press the recording medium stuck fast to the conveying belt closely to the conveying belt.

10 According to the present invention, the recording medium can be conveyed stably.

Additionally, in the recording-medium conveying device according to the present invention, the AC bias may be impressed to the belt charging unit when the recording medium is conveyed. Further, the AC bias is preferred to be stopped being impressed to the belt charging unit when the recording medium is stopped being conveyed.

Alternatively, in the recording-medium conveying device according to the present invention, the AC bias may be impressed to the belt charging unit while the conveying belt is continuously revolved, before the recording medium is conveyed.

In order to achieve the above-mentioned objects, there is also provided according to another

10092701-030002

aspect of the present invention a conveyance control device controlling one of the above-mentioned recording-medium conveying devices, the conveyance control device comprising:

5           a binary scale provided on a part of the conveying belt along the moving direction thereof, wherein one of a reflected light and a transmitted light from the binary scale is detected so as to control a revolving velocity and a stopping position of the driving roller.

10           Additionally, the conveyance control device according to the present invention may further comprise an optical sensor provided opposite a part of the conveying belt downstream from and near the driving roller so as to detect one of the reflected light and the transmitted light. Alternatively, the conveyance control device according to the present invention may further comprise an optical sensor provided opposite a part of the conveying belt corresponding to the image recording part so as to detect the reflected light.

15           In order to achieve the above-mentioned objects, there is also provided according to another aspect of the present invention a conveyance control device controlling one of the above-mentioned recording-  
25 medium conveying devices, the conveyance control device

202501.030702

comprising:

a conveyance distance detecting unit detecting one of a conveyance speed and a conveyance distance of the conveying belt; and

5 a conveying-belt driving unit driving the driving roller,

wherein the conveying-belt driving unit is controlled according to one of the conveyance speed and the conveyance distance detected by the conveyance  
10 distance detecting unit.

According to the present invention, the recording medium can be conveyed at a conveyance speed optimum for an image formation.

Additionally, in the conveyance control device  
15 according to the present invention, the conveyance distance detecting unit may comprise:

a binary scale provided on one of an outer surface and an inner surface of the conveying belt; and

a read sensor reading the binary scale,

20 wherein the binary scale has pitches arranged at an interval corresponding to a value obtained by dividing a maximum resolution of an image to be recorded on the recording medium by  $n$ , where  $n$  is an integer larger than zero.

25 Additionally, in the conveyance control device

10052701-0303  
202507102500F



according to the present invention, the conveyance distance detecting unit may comprise an encoder provided on a rotary shaft of the driving roller,

wherein the driving roller has a diameter  
5 determined such that a conveyance distance of the conveying belt corresponding to one pulse output by the encoder becomes a value obtained by dividing a maximum resolution of an image to be recorded on the recording medium by n, where n is an integer larger than zero.

10 According to the present invention, the feed distance (the conveyance distance) of the conveying belt electrostatically absorbing the recording medium can be controlled according to a unit distance corresponding to the maximum resolution. Accordingly, in an inkjet  
15 printer of a serial type, a precision of starting a new print line can be controlled with high precision, and in an inkjet printer of a line type, a speed of starting a new print line can be controlled with high precision. Therefore, a high-quality image can be stably formed on  
20 the recording medium.

In order to achieve the above-mentioned objects, there is also provided according to another aspect of the present invention an inkjet recording device comprising:

25 a recording head (mounted on a carriage) in an

10092701-03000

image recording part so as to record an image by jetting ink drops on a recording medium;

a recording-medium feeding device containing the recording medium, and separating and feeding the recording medium one by one therefrom by a separating unit thereof; and

one of the above-mentioned recording-medium conveying devices.

In order to achieve the above-mentioned objects, there is also provided according to another aspect of the present invention an inkjet recording device comprising:

a recording head mounted on a carriage in an image recording part so as to record an image by jetting ink drops on a recording medium;

a recording-medium feeding device containing the recording medium, and separating and feeding the recording medium one by one therefrom; and

one of the above-mentioned recording-medium conveying devices.

Other objects, features and advantages of the present invention will become more apparent from the following detailed description when read in conjunction with the accompanying drawings.

BRIEF DESCRIPTION OF THE DRAWINGS

FIG.1 is an illustration of a configuration of an inkjet printer according to a first embodiment of the present invention;

5           FIG.2 is an illustration of a configuration of a recording-sheet conveying device shown in FIG.1;

FIG.3 is a cross-sectional view of a structure of a conveying belt shown in FIG.2;

10           FIG.4A and FIG.4B are a sectional view and a top view including the conveying belt and conveyance guides shown in FIG.2;

FIG.5 is an illustration of micro electric fields generated by electric charges charged in the conveying belt;

15           FIG.6 is an illustration of a configuration of a recording-sheet conveying device according to a second embodiment of the present invention;

20           FIG.7 is an illustration of a configuration of a recording-sheet conveying device according to a third embodiment of the present invention;

FIG.8A is an illustration of a first arrangement of an optical sensor provided in the recording-sheet conveying device shown in FIG.7;

25           FIG.8B is an illustration of a second arrangement of the optical sensor provided in the

2009201-030702

recording-sheet conveying device shown in FIG.7;

FIG.9 is a block diagram of a control unit for controlling a driving roller shown in FIG.7;

FIG.10 is an illustration of a configuration  
5 of a recording-sheet conveying device according to a fourth embodiment of the present invention;

FIG.11 is a perspective view of a grip roller;

FIG.12 is a perspective view of a timing belt formed at the inner side of the conveying belt;

10 FIG.13 is an illustration of a configuration of a recording-sheet conveying device according to a fifth embodiment of the present invention;

FIG.14A and FIG.14B are a sectional view and a top view including a conveying belt and a conveyance  
15 guide shown in FIG.13;

FIG.15 is an illustration of electric charges charged in the conveying belt by applying an AC bias;

FIG.16 is an illustration of micro electric fields generated by the electric charges charged in the  
20 conveying belt;

FIG.17 is an illustration of a configuration of an inkjet printer according to a six embodiment of the present invention;

FIG.18 is an illustration of a configuration  
25 of a recording-sheet conveying device shown in FIG.17;

10092701.030702

25 FIG.26A and FIG.26B are a front view and a

magnified view of an arrangement of a scale provided on a disc included in the rotary encoder shown in FIG.25;

FIG.27A and FIG.27B are perspective views of slippage prevention mechanisms provided between the driving roller and the conveying belt;

FIG.28A is a perspective view of a configuration of a line head;

FIG.28B is a front view of a line of nozzles of the line head shown in FIG.28A; and

FIG.29 is an illustration of a configuration of an inkjet printer of a line type including the line head shown in FIG.28A.

#### DETAILED DESCRIPTION OF THE PREFERRED EMBODIMENTS

A description will now be given, with reference to the drawings, of embodiments according to the present invention.

[Embodiments 1-4]

FIG.1 is an illustration of a configuration of an inkjet printer according to a first embodiment of the present invention. As shown in FIG.1, an inkjet printer 1 comprises four ink cartridges 2, four recording heads 3, a carriage 4, feeding trays 5a and 5b, a manual feeding tray 6, a recording-sheet conveying device 8, a delivery tray 9, and a delivery roller 10. The four ink

cartridges 2 contain four inks of cyan C, magenta M,  
yellow Y, and black Bk, respectively. The four  
recording heads 3 have a plurality of nozzles, and are  
supplied with the inks from the four ink cartridges 2,  
5 respectively. The ink cartridges 2 and the recording  
heads 3 are mounted on the carriage 4. The feeding  
trays 5a and 5b contain recording sheets. The feeding  
trays 5a and 5b and the manual feeding tray 6 form a  
recording-medium feeding device. The recording-sheet  
10 conveying device 8 conveys a recording sheet from the  
feeding trays 5a, 5b, or the manual feeding tray 6 to a  
printing part (an image recording part) 7 including the  
recording heads 3. The delivery roller 10 delivers a  
printed recording sheet to the delivery tray 9. Upon  
15 printing image data transmitted from a host device on  
the recording sheet, ink drops are jetted from the  
nozzles of the recording heads 3 on the recording sheet  
according to the image data so as to record a character  
or an image, while the carriage 4 performs a scanning  
20 guided by carriage guide rollers 11. In this course,  
the recording sheet is conveyed to the printing part 7  
by the recording-sheet conveying device 8.

As shown in FIG.2, the recording-sheet  
conveying device 8 comprises a conveying belt 14, a  
25 pressing roller 15, conveyance guides 16, and a belt

charging roller (a belt charging unit) 19. The conveying belt 14 is wound around a driving roller 12 and a driven roller 13, and is capable of moving back and forth. The pressing roller 15 presses the conveying belt 14 against the driving roller 12 by exerting an elastic force of an elastic material such as a spring so as to prevent the conveying belt 14 from slipping on the driving roller 12. The conveyance guides 16 are arranged between the driving roller 12 and the driven roller 13 along a stretch nearer to the recording heads 3. A separating unit 18 separates and feeds a recording sheet 17 from other recording sheets contained in the feeding tray 5a. The belt charging roller 19 is so arranged in the vicinity of the separating unit 18 as to contact the conveying belt 14. As shown in FIG.3, the conveying belt 14 has a two-layer structure composed of an insulating layer 20 and a conductive layer 21. The insulating layer 20 is formed at the outer side of the two-layer structure contacting the recording sheet 17 and the belt charging roller 19. The conductive layer 21 is formed at the inner side of the two-layer structure not contacting the recording sheet 17 or the belt charging roller 19. As shown in a sectional view of FIG.4A and a top view of FIG.4B, the conveying belt 14 is narrower than the recording sheet 17, and is wound



around central parts of the driving roller 12 and the driven roller 13. The conveyance guides 16 are arranged at both sides of the conveying belt 14 in a widthwise direction thereof, and have a plurality of ribs 22 and  
5 recession grooves 23 arranged alternately. Each of the ribs 22 and the recession grooves 23 is aligned along a direction (a conveying direction of the recording sheet 17) in which the recording sheet 17 is conveyed. As shown in FIG.3, the belt charging roller 19 is connected  
10 to an AC bias applying unit 24 applying an AC bias of, for example, 2 kV to 3 kV.

When the inkjet printer 1 receives an instruction for outputting an image, the driving roller 12 of the recording-sheet conveying device 8 is revolved  
15 by a driving motor (not shown in the figures) so that the conveying belt 14 is revolved counterclockwise. At the same time, the AC bias is applied from the AC bias applying unit 24 to the belt charging roller 19. By this AC bias applied to the belt charging roller 19, the  
20 insulating layer 20 of the conveying belt 14 is charged with positive charges and negative charges alternately in a direction (a moving direction of the conveying belt 14) in which the conveying belt 14 moves, as shown in FIG.3. When the recording sheet 17 separated and fed by  
25 the separating unit 18 contacts the conveying belt 14,

the recording sheet 17 is subjected to electrostatic forces originating from micro electric fields 25 each induced from the positive charge to the negative charge charged in the insulating layer 20 of the conveying belt 14, as shown in FIG.5. These electrostatic forces cause a central part of the recording sheet 17 to stick fast to the conveying belt 14. Therefor, the belt charging roller 19 charging the conveying belt 14 positively and negatively is arranged in the vicinity of the separating unit 18 feeding the recording sheet 17 from the feeding tray 5a; thereby, the micro electric fields 25 are surely generated so that the recording sheet 17 is stably stuck fast to the conveying belt 14.

The recording sheet 17 stuck fast to the conveying belt 14 is conveyed to the printing part 7 as the conveying belt 14 revolves. Then, when an image formation area at a leading part of the recording sheet 17 reaches a position right under the recording heads 3, the driving roller 12 is stopped revolving so that the conveying belt 14 is stopped revolving. In this state where the recording sheet 17 is stopped, ink drops are jetted from the recording heads 3 while the recording heads 3 are moved back and forth in scanning directions by the carriage 4 so as to form an image on the recording sheet 17. Then, when this image formation for

the image formation area at the leading part of the recording sheet 17 is completed, the driving roller 12 is restarted so as to revolve the conveying belt 14.

The recording sheet 17 is conveyed until a following

5 image formation area of the recording sheet 17 reaches the position right under the recording heads 3.

Thereupon, the driving roller 12 is stopped revolving so as to stop the conveying belt 14. In this state, an

image is formed on the following image formation area of

10 the recording sheet 17. Thus, the conveying belt 14 repeats the conveyance and stoppage of the recording sheet 17 so as to form an image on the recording sheet 17.

While the conveyance and stoppage of the

15 recording sheet 17 is repeated so as to form an image on the recording sheet 17, the recording sheet 17 is stuck fast to the conveying belt 14 by the electrostatic forces originating from the micro electric fields 25.

Furthermore, the conveying belt 14 is constantly pressed

20 against the driving roller 12 by the pressing roller 15 so as to increase a frictional force between the driving roller 12 and the conveying belt 14 to prevent the conveying belt 14 from slipping on the driving roller 12.

Accordingly, the recording sheet 17 can be conveyed and

25 stopped with precision. Additionally, the recording

10092701-030703

sheet 17 is stuck fast to the conveying belt 14 by the electrostatic forces originating from the micro electric fields 25 discontinuously generated by the positive charges and the negative charges charged alternately in the conveying belt 14 at a constant interval of 4 mm, for example. This eliminates influences of the electrostatic forces otherwise posed on the ink drops jetted from the recording heads 3 so that the ink drops are jetted onto predetermined landing spots. Thereby, a high-quality image without positional displacement can be stably formed on the recording sheet 17.

While the ink drops are jetted from the recording heads 3 onto the recording sheet 17 so as to form an image thereon, the ink drops permeate the recording sheet 17 so that the recording sheet 17 is elongated, causing a cockling in the recording sheet 17. However, this elongated recording sheet 17 is kept at its original height by the ribs 22 of the conveyance guides 16 whereas other parts of the elongated recording sheet 17 sags into the recession grooves 23 where the ribs 22 do not exist, as shown in FIG.4A. This prevents an elevation of the recording sheet 17 soaking the ink drops. Accordingly, this prevents influences of the cockling from displacing the landing spots of the ink drops on the recording sheet 17. This also prevents the

10092701-030702

recording sheet 17 from contacting the nozzles of the recording heads 3; thereby, the nozzles of the recording heads 3 are prevented from becoming dirty, and the recording sheet 17 is prevented from being smeared.

5 Accordingly, a high-quality image can be stably formed on the recording sheet 17.

10 This recording sheet 17 on which an image is formed as described above is conveyed downstream from the recording heads 3 by the conveying belt 14. When the conveying belt 14 changes its direction around the driving roller 12, the recording sheet 17 is separated from the conveying belt 14 by its own rigidity toward the delivery roller 10. In this course, the recording sheet 17 can be easily separated from the conveying belt 15 14 without a need for a complicated recording-sheet separation mechanism, because the recording sheet 17 is stuck to the conveying belt 14 only by the electrostatic forces originating from the micro electric fields 25 discontinuously generated by the positive charges and 20 the negative charges charged alternately in the conveying belt 14 at a constant interval. In addition, since only the discontinuously generated micro electric fields 25 are applied to the recording sheet 17, the electrostatic forces are prevented from remaining in the 25 delivered recording sheet 17.

10092701-030702

The above-described first embodiment sets forth an example where the driving roller 12 and the driven roller 13 have substantially the same diameter. However, as in a second embodiment of the recording-sheet conveying device 8 shown in FIG.6, it is preferred that the driven roller 13 provided near the separating unit 18 has a large diameter and the driving roller 12 provided near the delivery roller 10 has a small diameter. Enlarging the diameter of the driven roller 13, which is provided at a side where the recording sheet 17 is stuck to the conveying belt 14, increases a radius of curvature at which the conveying belt 14 changes its direction so as to decrease a bending stress imposed on the recording sheet 17 stuck fast thereto. Thereby, the recording sheet 17 stuck fast to the conveying belt 14 can be bent naturally from the leading part of the recording sheet 17 so that the recording sheet 17 can be conveyed stably. On the other hand, decreasing the diameter of the driving roller 12, which is provided on a side where the recording sheet 17 is separated from the conveying belt 14, reduces a radius of curvature at which the conveying belt 14 changes its direction. Accordingly, the recording sheet 17 can be easily separated from the conveying belt 14 by its own rigidity.

When the conveying belt 14 conveys the recording sheet 17 stuck fast thereto to right under the recording heads 3, and intermittently repeats the revolution and stoppage thereof, the conveying belt 14 needs to be controlled to stop at a precise position. Therefor, for example, as in a third embodiment of the recording-sheet conveying device 8 shown in FIG.7, periodical bumps and dents may be formed on a part of the conveying belt 14 at an interval selected from a range of 10  $\mu\text{m}$  to 100  $\mu\text{m}$  in accordance with a precision required in conveying the recording sheet 17, or a binary scale 26 having periodically changing optical reflectance and transmittance may be provided on a part of the conveying belt 14. Then, a light reflected on the binary scale 26 may be detected by an optical sensor 27 of a reflection type or a transmission type provided at a part free from influences of an extension of the conveying belt 14 downstream from the driving roller 12, as shown in FIG.8A, or of a transmission type provided in the vicinity of the printing part 7, as shown in FIG.8B, so as to control the revolution and stoppage of the driving roller 12. For example, the revolution and stoppage of the driving roller 12 can be controlled by a control unit (a conveyance control device) 40 shown in a block diagram of FIG.9. In FIG.9, a processing circuit

29 receives a drive instruction signal, and computes a revolving velocity and a stopping position of a servomotor 28 revolving and stopping the driving roller 12. In this course, a stopping-position signal is transmitted from the optical sensor 27 to the processing circuit 29 so as to control the stopping position. Also, a velocity signal is transmitted from the optical sensor 27 to a servomotor drive circuit 30 driving the servomotor 28 so as to control the revolving velocity of the servomotor 28 at a constant velocity. Thus, by controlling the revolving velocity and the stopping position of the servomotor 28 revolving and stopping the driving roller 12, the recording sheet 17 stuck fast to the conveying belt 14 can be controlled to stop at a precise position, and therefore, a stable image can be formed. In addition, by using the binary scale 26 provided on the conveying belt 14 to directly detect a conveyance distance of the conveying belt 14 so as to control the revolution of the driving roller 12 as described above, the pressing roller 15 may be provided between a sheet conveying roller 31 and a pressuring roller 32, as in a fourth embodiment of the recording-sheet conveying device 8 shown in FIG.10, so as to prevent the conveying belt 14 from slipping on the driven roller 13.



Additionally, in the embodiments according to the present invention, the conveying belt 14 is pressed against the driving roller 12 or the driven roller 13 by the pressing roller 15 so as to prevent the conveying belt 14 from slipping on the driving roller 12 or the driven roller 13 to increase a positional precision of stopping the conveying belt 14. Furthermore, the surface of the driving roller 12 or the driven roller 13 may be subjected to a curing process, such as a urethane coating, so as to increase the frictional force between the driving roller 12 or the driven roller 13 and the conveying belt 14 to surely prevent the conveying belt 14 from slipping on the driving roller 12 or the driven roller 13. Thereby, the recording sheet 17 not only can be stably conveyed, but also can be controlled to stop at a precise position.

Further, as shown in a perspective view of FIG.11, the driving roller 12 or the driven roller 13 may be formed as a grip roller 34 having a plurality of projections 33. Also as shown in a perspective view of FIG.12, a timing belt 35 may be formed throughout the inner side of the conveying belt 14 not contacting the recording sheet 17. By these arrangements, the conveying belt 14 is surely prevented from slipping on the driving roller 12 or the driven roller 13 so that

the recording sheet 17 can be controlled to stop at a precise position in the course of forming an image thereon. Alternatively, the timing belt 35 may be formed at a part of the inner side of the conveying belt 14 not contacting the recording sheet 17. This arrangement prevents the conveying belt 14 from moving sideways so that the conveying belt 14 is revolved stably.

[Embodiment 5]

FIG.13 is an illustration of a configuration of a recording-sheet conveying device according to a fifth embodiment of the present invention. As shown in FIG.13, a recording-sheet conveying device 108 comprises a conveying belt 114, a belt charging roller (a belt charging unit) 115, a pressing roller 116, and a conveyance guide 117. The conveying belt 114 is wound around a driving roller 112 and a driven roller 113, and is capable of moving back and forth. The driving roller 112 is connected to a ground. A surface of the conveying belt 114 contacting the belt charging roller 115 is formed of an insulating layer. As shown in a sectional view of FIG.14A and a top view of FIG.14B, the conveying belt 114 is narrower than the recording sheet 17, and is wound around central parts of the driving roller 112 and the driven roller 113. The belt charging

roller 115 is arranged opposite the driving roller 112 at a position upstream in a revolving direction of the driving roller 112, i.e., upstream from a position at which the recording sheet 17 separated and fed by the separating unit 18 of the feeding tray 5a along a guide portion 121 contacts the conveying belt 114 wound around the driving roller 112. The belt charging roller 115 is connected to an AC bias applying unit 122 applying an AC bias of, for example, 2 kV to 3 kV. The pressing roller 116 is composed of an insulating material, and is arranged opposite the driving roller 112 at a position downstream in the revolving direction of the driving roller 112 from the belt charging roller 115 and upstream in the conveying direction of the recording sheet 17 from the recording heads 3. The pressing roller 116 presses the recording sheet 17 against the conveying belt 114 by exerting an elastic force of an elastic material such as a spring. The conveyance guide 117 is arranged between the driving roller 112 and the driven roller 113 along the conveying belt 114 opposite the recording heads 3 across the conveying belt 114. As shown in FIG.14A and FIG.14B, the conveyance guide 117 has a plurality of ribs 123 and recession grooves 124 alternately arranged at both sides of the conveying belt 114 in a widthwise direction thereof. Each of the

ribs 123 and the recession grooves 124 is aligned along the conveying direction of the recording sheet 17.

Upon feeding the recording sheet 17 when the inkjet printer 1 including the above-described

5 recording-sheet conveying device 108 receives an instruction for outputting an image, the driving roller 112 is revolved by a driving motor (not shown in the figures) so that the conveying belt 114 is revolved counterclockwise. At the same time, the AC bias is  
10 applied from the AC bias applying unit 122 to the belt charging roller 115. When the AC bias is applied to the belt charging roller 115, the insulating layer of the conveying belt 114 flanked by the belt charging roller 115 and the driving roller 112 connected to the ground  
15 is charged with positive charges and negative charges alternately in a moving direction of the conveying belt 114, as shown in FIG.15. When the recording sheet 17 separated and fed by the separating unit 18 contacts the conveying belt 114, the recording sheet 17 is subjected  
20 to electrostatic forces originating from micro electric fields 125 each induced from the positive charge to the negative charge charged in the conveying belt 114, as shown in FIG.16. These electrostatic forces cause a central part of the recording sheet 17 to stick fast to  
25 the conveying belt 114. Therefor, the belt charging

roller 115 charging the conveying belt 114 positively and negatively is arranged opposite the driving roller 112 connected to the ground; thereby, the micro electric fields 125 are surely generated. Additionally, since  
5 the belt charging roller 115 charging the conveying belt 114 positively and negatively is arranged at the position upstream in the conveying direction of the recording sheet 17 from the position at which the recording sheet 17 contacts the conveying belt 114 wound  
10 around the driving roller 112, the recording sheet 17 is stably stuck fast to the conveying belt 114.

The recording sheet 17 stuck fast to the conveying belt 114 is further pressed closely to the conveying belt 114 by the pressing roller 116. Since  
15 the pressing roller 116 is composed of an insulating material, the recording sheet 17 can be stuck to the conveying belt 114 while the positive charges and the negative charges charged in the conveying belt 114 are kept intact. The recording sheet 17 in this state is  
20 conveyed to the printing part 7 as the conveying belt 114 revolves. Then, when the image formation area at the leading part of the recording sheet 17 reaches a position right under the recording heads 3, the driving roller 112 is stopped revolving so that the conveying  
25 belt 114 is stopped revolving. In this state where the

recording sheet 17 is stopped, ink drops are jetted from the recording heads 3 while the recording heads 3 are moved back and forth in scanning directions by the carriage 4 so as to form an image on the recording sheet

5 17. Then, when this image formation for the image formation area at the leading part of the recording sheet 17 is completed, the driving roller 112 is restarted so as to revolve the conveying belt 114. The recording sheet 17 is conveyed until the following image formation area of the recording sheet 17 reaches the position right under the recording heads 3. Thereupon, the driving roller 112 is stopped revolving so as to stop the conveying belt 114. In this state, an image is formed on the following image formation area of the recording sheet 17. Thus, the conveying belt 114 repeats the conveyance and stoppage of the recording sheet 17 so as to form an image on the recording sheet 17.

While the conveyance and stoppage of the recording sheet 17 is repeated so as to form an image on the recording sheet 17, the recording sheet 17 is stuck fast to the conveying belt 114 by the electrostatic forces originating from the micro electric fields 125. Furthermore, the conveying belt 114 and the recording sheet 17 are constantly pressed against the driving

roller 112 by the pressing roller 116 so as to increase  
a frictional force between the driving roller 112 and  
the conveying belt 114 to prevent the conveying belt 114  
from slipping on the driving roller 112. Accordingly,  
5 the recording sheet 17 can be conveyed and stopped with  
precision. Additionally, the recording sheet 17 is  
stuck fast to the conveying belt 114 by the  
electrostatic forces originating from the micro electric  
fields 125 discontinuously generated by the positive  
10 charges and the negative charges charged alternately in  
the conveying belt 114 at a constant interval of 4 mm,  
for example. This eliminates influences of the  
electrostatic forces otherwise posed on the ink drops  
jetted from the recording heads 3 so that the ink drops  
15 are jetted onto predetermined landing spots. Thereby, a  
high-quality image without positional displacement can  
be stably formed on the recording sheet 17.

While the ink drops are jetted from the  
recording heads 3 onto the recording sheet 17 so as to  
20 form an image thereon, the ink drops permeate the  
recording sheet 17 so that the recording sheet 17 is  
elongated, causing a cockling in the recording sheet 17.  
However, this elongated recording sheet 17 is kept at  
its original height by the ribs 123 of the conveyance  
25 guide 117 whereas other parts of the elongated recording

10092701-030700

sheet 17 sags into the recession grooves 124 where the ribs 123 do not exist, as shown in FIG.14A. This prevents an elevation of the recording sheet 17 soaking the ink drops. Accordingly, this prevents influences of the cockling from displacing the landing spots of the ink drops on the recording sheet 17. This also prevents the recording sheet 17 from contacting the nozzles of the recording heads 3; thereby, the nozzles of the recording heads 3 are prevented from becoming dirty, and the recording sheet 17 is prevented from being smeared. Accordingly, a high-quality image can be stably formed on the recording sheet 17.

This recording sheet 17 on which an image is formed as described above is conveyed downstream from the recording heads 3 by the conveying belt 114. When the conveying belt 114 changes its direction around the driven roller 113, the recording sheet 17 is separated from the conveying belt 114 by its own rigidity toward the delivery roller 10. In this course, the recording sheet 17 can be easily separated from the conveying belt 114 without a need for a complicated recording-sheet separation mechanism, because the recording sheet 17 is stuck to the conveying belt 114 only by the electrostatic forces originating from the micro electric fields 125 discontinuously generated by the positive



charges and the negative charges charged alternately in the conveying belt 114 at a constant interval. In addition, since only the discontinuously generated micro electric fields 125 are applied to the recording sheet 17, the electrostatic forces are prevented from remaining in the delivered recording sheet 17.

In the above-described fifth embodiment, the AC bias is applied to the belt charging roller 115, even when the conveying belt 114 is stopped while ink drops are jetted from the recording heads 3 being moved back and forth in scanning directions by the carriage 4 so as to form an image on the recording sheet 17. However, the application of the AC bias to the belt charging roller 115 may be stopped, when the conveying belt 114 is stopped. Thereby, the charges charged at a part of the conveying belt 114 contacting the belt charging roller 115 are prevented from being removed by the AC bias; therefore, when the conveying belt 114 is revolved subsequently, the recording sheet 17 is stably stuck fast to the conveying belt 114.

Additionally, in the above-described fifth embodiment, the AC bias is applied to the belt charging roller 115 upon feeding the recording sheet 17 when the inkjet printer 1 receives an instruction for outputting an image. However, when the inkjet printer 1 receives

the instruction for outputting an image, the AC bias may be applied to the belt charging roller 115 beforehand while continuously revolving the conveying belt 114 so as to charge the conveying belt 114 with the positive charges and the negative charges, and then the recording sheet 17 may be fed after stopping the application of the AC bias to the belt charging roller 115 in the state where the entire conveying belt 114 is charged with the positive charges and the negative charges. Thus, charging the conveying belt 114 with the positive charges and the negative charges while continuously revolving the conveying belt 114 enables the conveying belt 114 to be charged stably.

[Embodiment 6]

FIG.17 is an illustration of a configuration of an inkjet printer according to a six embodiment of the present invention. As shown in FIG.17, an inkjet printer 201 of a serial type comprises four ink cartridges 202, a recording head 203, a carriage 204, feeding trays 205a and 205b, a manual feeding tray 206, a recording-sheet conveying device 208, a delivery tray 209, and a delivery roller 210. The four ink cartridges 202 contain four inks of cyan C, magenta M, yellow Y, and black Bk, respectively. The recording head 203 has a plurality of nozzles, and are supplied with the inks

from the four ink cartridges 202, respectively. The ink cartridges 202 and the recording head 203 are mounted on the carriage 204. The feeding trays 205a and 205b contain recording sheets. The feeding trays 205a and 205b and the manual feeding tray 206 form a recording-medium feeding device. The recording-sheet conveying device 208 conveys a recording sheet from the feeding trays 205a, 205b, or the manual feeding tray 206 to a printing part (an image recording part) 207 including the recording head 203. The delivery roller 210 delivers a printed recording sheet to the delivery tray 209. Upon printing image data transmitted from a host device on the recording sheet, ink drops are jetted from the nozzles of the recording head 203 on the recording sheet according to the image data so as to record a character or an image, while the carriage 204 performs a scanning guided by carriage guide rollers 211. In this course, the recording sheet is conveyed to the printing part 207 by the recording-sheet conveying device 208.

As shown in FIG.18, the recording-sheet conveying device 208 comprises a conveying belt 214, a pressing roller 215, conveyance guides 216, and a belt charging roller (a belt charging unit) 219. The conveying belt 214 is wound around a driving roller 212 and a driven roller 213, and is capable of moving back

and forth. The pressing roller 215 is pressed against a part of the conveying belt 214 wound around the driving roller 212 by an elastic force of an elastic material such as a spring so as to prevent the conveying belt 214 from slipping on the driving roller 212. The conveyance guides 216 are arranged between the driving roller 212 and the driven roller 213 along a stretch nearer to the recording head 203. The belt charging roller 219 is arranged opposite the driving roller 212, and contacts the conveying belt 214 at a position upstream in a revolving direction of the driving roller 212, i.e., upstream from a position at which the recording sheet 17 separated and fed from the feeding tray 205a by a separating unit 218 contacts the conveying belt 214 wound around the driving roller 212. The driving roller 212 is connected to a ground.

The conveying belt 214 has a one-layer structure, as shown in FIG.19A, or has a two-layer structure, as shown in FIG.19B. An insulating layer 220 is formed at the outer side of the two-layer structure contacting the recording sheet 17 and the belt charging roller 219. When the conveying belt 214 has the two-layer structure, a conductive layer 221 is formed at the inner side of the two-layer structure not contacting the recording sheet 17 or the belt charging roller 219. The

insulating layer 220 is formed of a resin or an elastomer, such as PET, PEI, PVDF, PC, ETFE, or PTFE, not containing a conductive control material so as to have a volume resistivity of  $10^{12} \Omega\text{cm}$  or more,

5 preferably  $10^{15} \Omega\text{cm}$ . The conductive layer 221 is formed of the above-mentioned resin or the elastomer containing a carbon so as to have a volume resistivity of  $10^5$  to  $10^7 \Omega\text{cm}$ .

As shown in a sectional view of FIG.20A and a  
10 top view of FIG.20B, the conveying belt 214 is narrower than the recording sheet 17, and is wound around central parts of the driving roller 212 and the driven roller 213. The conveyance guides 216 are arranged at both  
15 sides of the conveying belt 214 in a widthwise direction thereof, and have a plurality of ribs 222 and recession grooves 223 arranged alternately. Each of the ribs 222 and the recession grooves 223 is aligned along a direction (a conveying direction of the recording sheet 17) in which the recording sheet 17 is conveyed. As  
20 shown in FIG.19A and FIG.19B, the belt charging roller 219 is connected to an AC bias applying unit 224 applying an AC bias of, for example, 2 kV to 3 kV.

When the inkjet printer 201 of the serial type receives an instruction for outputting an image, the  
25 driving roller 212 of the recording-sheet conveying

device 208 is revolved by a driving motor (not shown in the figures) so that the conveying belt 214 is revolved counterclockwise. At the same time, the AC bias is applied from the AC bias applying unit 224 to the belt charging roller 219. By this AC bias applied to the belt charging roller 219, the insulating layer 220 of the conveying belt 214 is charged with positive charges and negative charges alternately in a direction (a moving direction of the conveying belt 214) in which the conveying belt 214 moves, as shown in FIG.19A and FIG.19B. Since this insulating layer 220 of the conveying belt 214 charged with the positive charges and the negative charges is so formed as to have the volume resistivity of  $10^{12} \Omega\text{cm}$  or more, preferably  $10^{15} \Omega\text{cm}$ , the positive charges and the negative charges alternately charged in the insulating layer 220 are prevented from moving across boundaries therebetween so that the insulating layer 220 can be charged stably with the positive charges and the negative charges alternately.

When the recording sheet 17 separated and fed by the separating unit 218 contacts the conveying belt 214, the recording sheet 17 is subjected to electrostatic forces originating from micro electric fields 225 each induced from the positive charge to the negative charge charged in the insulating layer 220 of

the conveying belt 214, as shown in FIG.21A and FIG.21B. These electrostatic forces cause a central part of the recording sheet 17 to stick fast to the conveying belt 214. Therefor, the belt charging roller 219 charging  
5 the conveying belt 214 positively and negatively is arranged at the position upstream in the revolving direction of the driving roller 212 in the vicinity of the position at which the recording sheet 17 fed by the separating unit 218 contacts the conveying belt 214;  
10 thereby, the micro electric fields 25 are surely generated at the position at which the recording sheet 17 contacts the conveying belt 214 so that the recording sheet 17 is stably stuck fast to the conveying belt 214. Additionally, the recording sheet 17 can be conveyed  
15 while the evenness of a print surface thereof is maintained without being pressed by a spur, etc. Therefore, not only a high-quality image can be stably formed on the recording sheet 17, but also the print surface of the recording medium can be prevented from  
20 being smeared or damaged.

The recording sheet 17 stuck fast to the conveying belt 214 is conveyed to the printing part 207 by the revolution of the conveying belt 214 while the recording sheet 17 is pressed by the pressing roller 215.  
25 Then, when the image formation area at the leading part

1009201-0000

of the recording sheet 17 reaches a position right under the recording head 203, the driving roller 212 is stopped revolving so that the conveying belt 214 is stopped revolving. In this state where the recording sheet 17 is stopped, ink drops are jetted from the recording head 203 while the recording head 203 are moved back and forth in scanning directions by the carriage 204 so as to form an image on the recording sheet 17. Then, when this image formation for the image formation area at the leading part of the recording sheet 17 is completed, the driving roller 212 is restarted so as to revolve the conveying belt 214. The recording sheet 17 is conveyed until the following image formation area of the recording sheet 17 reaches the position right under the recording head 203. Thereupon, the driving roller 212 is stopped revolving so as to stop the conveying belt 214. In this state, an image is formed on the following image formation area of the recording sheet 17. Thus, the conveying belt 214 repeats the conveyance and stoppage of the recording sheet 17 so as to form an image on the recording sheet 17.

While the conveyance and stoppage of the recording sheet 17 is repeated so as to form an image on the recording sheet 17, the recording sheet 17 is stuck



fast to the conveying belt 214 by the electrostatic forces originating from the micro electric fields 225. Additionally, since the recording sheet 17 stuck fast electrostatically to the conveying belt 214 is

5 constantly pressed against the conveying belt 214 by the pressing roller 215, the recording sheet 17 adheres closely to the conveying belt 214 so that the recording sheet 17 can be conveyed stably to the position right under the recording head 203. Also, the conveying belt

10 214 is constantly pressed against the driving roller 212 by the pressing roller 215 so as to increase a frictional force between the driving roller 212 and the conveying belt 214 to prevent the conveying belt 214 from slipping on the driving roller 212. Accordingly,

15 the recording sheet 17 can be conveyed and stopped with precision. Additionally, the recording sheet 17 is stuck fast to the conveying belt 214 by the electrostatic forces originating from the micro electric fields 225 discontinuously generated by the positive

20 charges and the negative charges charged alternately in the conveying belt 214 at a constant interval of 4 mm, for example. This prevents influences of the electrostatic forces from being posed on the ink drops jetted from the recording head 203 so that the ink drops

25 are jetted onto predetermined landing spots. Thereby, a

high-quality image without positional displacement can be stably formed on the recording sheet 17.

While the ink drops are jetted from the recording head 203 onto the recording sheet 17 so as to form an image thereon, the ink drops permeate the recording sheet 17 so that the recording sheet 17 is elongated, causing a cockling in the recording sheet 17. However, this elongated recording sheet 17 is kept at its original height by the ribs 222 of the conveyance guides 216 whereas other parts of the elongated recording sheet 17 sags into the recession grooves 223 where the ribs 222 do not exist, as shown in FIG.20A. This prevents an elevation of the recording sheet 17 soaking the ink drops, without pressing a print surface of the recording sheet 17. Accordingly, this prevents influences of the cockling from displacing the landing spots of the ink drops on the recording sheet 17. This also prevents the recording sheet 17 from contacting the nozzles of the recording head 203; thereby, the nozzles of the recording head 203 are prevented from becoming dirty, and the recording sheet 17 is prevented from being smeared. Accordingly, a high-quality image can be stably formed on the recording sheet 17.

This recording sheet 17 on which an image is formed as described above is conveyed downstream from

the recording head 203 by the conveying belt 214. When the conveying belt 214 changes its direction around the driven roller 213, the recording sheet 17 is separated from the conveying belt 214 by its own rigidity toward the delivery roller 210. In this course, the recording sheet 17 can be easily separated from the conveying belt 214 without a need for providing a complicated recording-sheet separation mechanism, because the recording sheet 17 is stuck to the conveying belt 214 only by the electrostatic forces originating from the micro electric fields 225 discontinuously generated by the positive charges and the negative charges charged alternately in the conveying belt 214 at a constant interval. In addition, since only the discontinuously generated micro electric fields 225 are applied to the recording sheet 17, the electrostatic forces are prevented from remaining in the delivered recording sheet 17. Further, when the conveying belt 214 has the two-layer structure of the insulating layer 220 and the conductive layer 221, the positive charges and the negative charges charged in the insulating layer 220 are discharged to some extent while the conveying belt 214 moves from the position right under the recording head 203 to the driven roller 213. Therefore, the recording sheet 17 can be easily separated from the conveying belt

214.

In the above-described sixth embodiment, the AC bias is applied to the belt charging roller 219, even when the conveying belt 214 is stopped while ink drops are jetted from the recording head 203 being moved back and forth in scanning directions by the carriage 204 so as to form an image on the recording sheet 17. However, the application of the AC bias to the belt charging roller 219 may be stopped, when the conveying belt 214 is stopped. This function prevents the AC bias from removing the charges charged at a part of the conveying belt 214 contacting the belt charging roller 219, and also prevents charges from being charged in unintended directions; therefore, when the conveying belt 214 is revolved subsequently, the recording sheet 17 is stably stuck fast to the conveying belt 214. Besides, although only a slight electric current flows in the charged conveying belt 214, there is a risk of heat being generated in the conveying belt 214 so as to induce a pin hole which may result in a leak, when one particular part of the conveying belt 214 is continuously charged. However, the above-mentioned function of stopping the application of the AC bias prevents the conveying belt 214 from being damaged.

Additionally, in the above-described sixth

embodiment, the pressing roller 215 is composed of an insulating material, and the AC bias is applied to the belt charging roller 219 upon feeding the recording sheet 17 when the inkjet printer 201 receives an instruction for outputting an image. However, when the inkjet printer 201 receives the instruction for outputting an image, the AC bias may be applied to the belt charging roller 219 beforehand while continuously revolving the conveying belt 214 so as to charge the conveying belt 214 with the positive charges and the negative charges, and then the recording sheet 17 may be fed after stopping the application of the AC bias to the belt charging roller 219 in the state where the entire conveying belt 214 is charged with the positive charges and the negative charges. Thus, charging the conveying belt 214 with the positive charges and the negative charges while continuously revolving the conveying belt 214 enables the conveying belt 214 to be stably charged with the positive charges and the negative charges.

When the conveying belt 214 of the inkjet printer 201 of the serial type conveys the recording sheet 17 to the position right under the recording head 203, and intermittently repeats the revolution and stoppage thereof, the conveying belt 214 needs to be controlled to stop at a precise position so as to

stabilize a precision of starting a new print line on the recording sheet 17. Therefor, a feed speed (a conveyance speed) or a feed distance (a conveyance distance) of the conveying belt 214 is directly or indirectly detected so that a conveyance distance of the conveying belt 214 is controlled according to the detected feed speed or the feed distance.

For example, in order that the feed speed or the feed distance of the conveying belt 214 is directly detected, an encoder (a conveyance distance detecting unit) 228 including a binary scale 226 and a read sensor 227 shown in a block diagram of FIG.24 may be used. The binary scale 226 has pitches formed on a part of the outer surface or the inner surface of the conveying belt 214 at an interval in accordance with a maximum resolution of the inkjet printer 201, as shown in a magnified view (FIG.22A) and a front view (FIG.22B) of the conveying belt 214. The read sensor 227 is of a transmission type or a reflection type provided at a part that does not influence the conveyance of the recording sheet 17 by the conveying belt 214, as shown in FIG.23A, or of a transmission type provided in the vicinity of the printing part 207, as shown in FIG.23B. In a drive control unit (a conveyance control device) 400 shown in FIG.24, a processing circuit 230 receives a

drive instruction signal, and computes a revolving velocity of a servomotor (a conveying-belt driving unit) 229 revolving the driving roller 212. In this course, a pulse signal is transmitted from the read sensor 227 to the processing circuit 230 so that the processing circuit 230 calculates the feed speed of the conveying belt 214. Then, a feed-speed signal representing the calculated feed speed is transmitted from the processing circuit 230 to a servomotor drive circuit 231 driving the servomotor 229 so as to control the revolving velocity of the servomotor 229 at a constant velocity. Thus, the driving roller 212 is revolved. As described above, by controlling the revolving velocity of the servomotor 229 revolving the driving roller 212, the conveyance distance of the recording sheet 17 can be controlled with precision.

The interval between the pitches of the binary scale 226 of the encoder 228 formed on the conveying belt 214 is a unit of precision of feeding the recording sheet 17. Additionally, a distance of feeding the recording sheet 17 to start a new print line corresponds to a minimum unit of the maximum resolution (a dot length) of the inkjet printer 201. For example, assuming that the maximum resolution of the inkjet printer 201 is 1200 dpi, a minimum unit distance of

feeding the recording sheet 17 to start a new print line  
is determined according to the maximum resolution, as  
 $25.4 \text{ mm} / 1200 = 21.2 \text{ } \mu\text{m}$ . Thereupon, the interval  
between the pitches of the binary scale 226, i.e., a  
5 unit distance for controlling the feed distance, is made  
as  $21.2 \text{ } \mu\text{m} / n$ , where  $n$  is an integer larger than zero.  
For example, assuming that  $n$  is 2, the interval between  
the pitches of the binary scale 226 becomes  $10.6 \text{ } \mu\text{m}$ .  
Accordingly, when the feed distance of the conveying  
10 belt 214 is controlled according to the pulse signal  
transmitted from the read sensor 227 reading the binary  
scale 226, a displacement by one pulse does not  
influence the image formed on the recording sheet 17;  
thus, a high-quality image can be stably formed.

15           On the other hand, in order that the feed  
speed or the feed distance of the conveying belt 214 is  
indirectly detected, a rotary encoder (conveyance  
distance detecting unit) 235 may be used so as to detect  
a revolving distance of the driving roller 212 and  
20 calculate the feed speed or the feed distance of the  
conveying belt 214. The rotary encoder 235 includes a  
disc 232, a scale 233 and a read sensor 234 of a  
transmission type or a reflection type. The disc 232 is  
provided on a rotary shaft of the driving roller 212  
25 driving the conveying belt 214, as shown in FIG.25. The



scale 233 has pitches (lines) arranged on the disc 232 in a circumferential direction thereof at a constant interval, as shown in a front view of FIG.26A and a magnified view of FIG.26B. The read sensor 234 reads the scale 233. In general, a scale pitch P of a rotary encoder is of 100 LPI, 150 LPI, 200 LPI, 300 LPI, and so forth. A well-known rotary encoder outputs pulses four times as many as an actual scale pulse. In an instance of the scale 233 having 2400 lines per revolution, the read sensor 234 capable of the above-mentioned fourfold output can output 9600 pulses. Additionally, a distance of feeding the recording sheet 17 to start a new print line corresponds to a minimum unit of the maximum resolution (a dot length) of the inkjet printer 201. For example, assuming that the maximum resolution of the inkjet printer 201 is 600 dpi, a minimum unit of the feed distance is determined as  $25.4 \text{ mm} / 600 = 42.3 \text{ } \mu\text{m}$ . Actually, the recording sheet 17 is fed by an integral multiple of 42.3  $\mu\text{m}$ . In the inkjet printer 201, the feed distance of the conveying belt 214 is determined according to the maximum resolution thereof.

As a more specific example, assuming that the driving roller 212 driving the conveying belt 214 is controlled according to a fourfold pulse signal output by the rotary encoder 235 comprising the scale 233

having 2400 pitches per revolution, the number of pulses per revolution output by the rotary encoder 235 is  $2400 \times 4 = 9600$  pulses. Then, assuming that the maximum resolution of the inkjet printer 201 is 1200 dpi, a feed distance corresponding to one output pulse is  $25.4 \text{ mm} / 1200 = 21.2 \text{ } \mu\text{m}$ . Since one revolution of the driving roller 212 coincides with one revolution of the disc 232 having the scale 233, a diameter of the driving roller 212 is calculated to be 64.5 mm, based on the following relational expression.

$$(d \times \pi) / 9600 = 21.2 \text{ } \mu\text{m}$$

d: diameter of the driving roller 212

That is, using the driving roller 212 having the diameter of 64.5 mm, and the rotary encoder 235 comprising the scale 233 provided on the rotary shaft of the driving roller 212 and having 2400 pitches makes the feed distance corresponding to one pulse  $21.2 \text{ } \mu\text{m}$ .

In stead of using the feed distance of  $21.2 \text{ } \mu\text{m}$  corresponding to one output pulse obtained according to the maximum resolution, it is preferred that the diameter of driving roller 212 is determined such that a feed distance corresponding to one output pulse of the rotary encoder 235 becomes a value obtained by dividing the feed distance of  $21.2 \text{ } \mu\text{m}$  determined according to the maximum resolution by n (n is an integer larger than

one). For example, when n is 2, the diameter of the driving roller 212 is calculated to be 32.4 mm, based on the following relational expression.

$$(d \times \pi) / 9600 = 10.6 \mu\text{m}$$

5           d: diameter of the driving roller 212

That is, using the driving roller 212 having the diameter of 32.4 mm, and the rotary encoder 235 comprising the scale 233 provided on the rotary shaft of the driving roller 212 and having 2400 pitches makes the  
10 feed distance corresponding to one pulse 10.6  $\mu\text{m}$ .  
Accordingly, a displacement by one pulse in controlling the feed distance of the driving roller 212 does not influence the image formed on the recording sheet 17; thus, a highly precise image can be stably formed.

15           Further, a slippage prevention mechanism may be provided between the driving roller 212 and the conveying belt 214. For example, as shown in FIG.27A, both of the driving roller 212 and the driven roller 213, or only the driving roller 212, may be formed as a grip  
20 roller 236 having a plurality of projections 238 on the surface thereof. Also as shown in FIG.27B, the conveying belt 214 is formed by a timing belt 237.  
These slippage prevention mechanisms surely prevent the conveying belt 214 from slipping on the driving roller  
25 212 or the driven roller 213 so that the recording sheet

17 can be controlled to stop at a precise position in the course of forming an image thereon, and also can be conveyed reversely with high precision.

Besides, although the above-described sixth  
5 embodiment sets forth the inkjet printer 201 of the serial type, the recording-sheet conveying device 208 is similarly applicable to an inkjet printer of a line type using a line head. As shown in a perspective view (FIG.28A) of the line head and a front view (FIG.28B) of  
10 a line of nozzles, a line head 243 comprises a line of nozzles 240 extending from side to side in a widthwise direction of the recording sheet 17 so as to jet inks supplied from an ink supplying tube 241 throughout a printable width of the recording sheet 17 according to a  
15 drive signal output from head drive signal lines 242. As shown in FIG.29, the recording-sheet conveying device 208 is similarly applicable to an inkjet printer 201a of the line type using the line head 243 so as to convey the recording sheet 17 stuck fast electrostatically to  
20 the conveying belt 214 stably to and at the printing part 207 so that a high-quality image can be formed stably with a more precise feed speed.

The present invention is not limited to the specifically disclosed embodiments, and variations and  
25 modifications may be made without departing from the

scope of the present invention.

The present application is based on Japanese priority applications No. 2001-065926 filed on March 9, 2001, No. 2001-221049 filed on July 23, 2001, and No.

- 5 2001-388792 filed on December 21, 2001, the entire contents of which are hereby incorporated by reference.

2001-065926